





Ultra D-SLS

lift & slide doors


Sill Options



Standard version without insect screen




Protected version with insect screen



Ultra Glass has developed the Ultra D-SLS sliding doors for installations where the glass becomes heavier to accommodate oversized openings. In such case, this model offers all the qualities of the regular slider, plus an option for Lift & Slide functionality.

With the push of a finger, the elevated glass panel effortlessly glides in motion across a separate rail enabling heavy loads. When the operation is complete, the Lift & Slide mechanism allows the panel back in its track for an airtight seal.



Ultra D-SLS is certified by the internationally acclaimed institute NFRC 100/200/500 allowing the product to meet the demands of the United States and Europe.

Technical Specifications

Max Width We can accommodate any conventional or custom size	78 - 47/64"
Max Height We can accommodate any conventional or custom size	94"
Glass Thickness	3/4" – 1"


doors

Characteristics


- ★ Levers and Rollers Lift Panels off Sill
- ★ Free From Weather Stripping With Little Effort
- ★ Sill-supported Panels Run on Two Multi-roller Carriages
- ★ Resistant to Air and Water Infiltration
- ★ Dual Weather Seals at Top, Bottom, and Sides
- ★ Pocketing and Cornering Systems Available
- ★ Non-corrosive Multi-point Locking Hardware

Section drawings

standard



with screen



Thermal Performance



Air Tightness



Water Tightness



Wind Load

